

IN THE CLAIMS

1. (Currently Amended) Fluid supply unit, comprising especially a hydraulic supply unit, ~~with~~ and a pressure generator for the fluid, especially a pump for hydraulic fluid, and a pressure outlet, ~~wherein~~ further comprising a pressure booster (6) ~~is~~ installed between the pressure generator (2) and the pressure outlet (7) and ~~is~~ rigidly mechanically connected with the pressure generator (2)[[.]] wherein the pressure booster (6) is driven by a portion of the fluid generated by the pump.
2. (Currently Amended) Unit in accordance with Claim 1, wherein the pressure generator (2) and the pressure booster (6) are installed in a common housing, ~~in which~~ wherein the outlets ~~connections~~ (5, 7) ~~run~~ extend in the housing between the pressure generator (2) and the pressure booster (6).
3. (Previously Presented) Unit in accordance with Claim 2, wherein the housing is constructed of more than one part.
4. (Currently Amended) Unit in accordance with Claim 3,

wherein ~~each of~~ two of the housing parts ~~has~~ have a joining surface (4), ~~which~~ and wherein the joining surfaces together form an interface between the pressure generator (2) and the pressure booster (6).

5. (Currently Amended) Unit in accordance with ~~any of~~ Claim ~~1~~ 2, ~~wherein comprising~~ a tank (15) ~~is~~ rigidly connected with the combination of pressure generator (2) and pressure booster (6).
6. (Previously Presented) Unit in accordance with Claim 5, wherein the tank (15) is integrated in the housing.
7. (Previously Presented) Unit in accordance with Claim 1, wherein the pressure booster (6) is arranged in axial extension of the pressure generator (2).
8. (Currently Amended) Unit in accordance with Claim ~~1~~ 2, ~~wherein comprising~~ a motor (9) for driving the pressure generator (2), wherein the motor is rigidly mechanically connected with the pressure generator (2).
9. (Previously Presented) Unit in accordance with Claim 8,

wherein the motor (9) and the pressure generator (2) have a common shaft (11).

10. (Previously Presented) Unit in accordance with Claim 8, wherein the motor (9) is designed as an electric motor.

11. (Currently Amended) Unit in accordance with Claim 10, comprising ~~wherein~~ a battery (41) ~~is~~ housed in the housing.

12. (Previously Presented) Unit in accordance with Claim 1, wherein the pressure generator is designed as a pump (2) that has a set of gears (3).

13. (Currently Amended) Unit in accordance with Claim 1, wherein ~~at least some parts of~~ the pressure booster (6) ~~are~~ is at least partially made of light metal or plastic.

14. (Currently Amended) Unit in accordance with Claim 1, ~~wherein~~ comprising a low-pressure connection and a pressure relief valve (50) is arranged between the outlet of the pressure generator (2) and a low-pressure connection.